

e-1510X Smart Pump powered by hydrovar® X

Example Product Code

The various versions of the e-1510X line are identified by a product code number. This number is also the catalog number for the pump. The meaning of each digit in the product code number is shown below. NOTE: Not all combinations are possible.

Α	1	м	5	S	x	1	
							Seal Material
							(1) = BUNA/C/SC
							(2) = EPR SIC/SIC
							Motor/Drive
							(X) = hydrovar X+(High Tier)
							Voltage
							(R) = 200-240V (S) = 380-460V (3-phase only)
							Pole-Hz-Phase (4) = 4-60-3 (2000-4000RPM)*
							(5) = 4-60-3 (1200-2000RPM)*
							* The frequency (Hz) listed is the supply frequency.
							HP Rating (J) = 3 (R) = 10 (P) = 25
							(K) = 5.5 $(M) = 15$ $(Q) = 30$
							(L) = 7.5 $(N) = 20$
							Pump Size
							(1) = AD-7" (5) = BD-9.5" (10) = GC-13.5 (2) $AC = 7"$ (4) ED 14"
							(2) = AC-7" (6) = EB-11" (3) = A-7" (7) = G-13.5"
							(11) = BB-9.5'' (8) = E-11''
							(4) = BC-9.5'' $(9) = GB - 13.5''$
							Discharge Size
							(A) = 1.25" (E) = 3"
							(B) = 1.5" (F) = 4"
							(C) = 2" (G) = 5"
							(D) = 2.5" (H) = 6"
							Pump Series
							(1510X) = e-1510 with hydrovar X/X+ technolog
							(1531X) = e-1531 with hydrovar X/X+ technolog

Xylem Product Cybersecurity:

Xylem values your system security and the availability of your critical services. For more information on Xylem cybersecurity practices or to contact the cybersecurity team please visit xylem.com/security.

xylem Let's Solve Water Xylem Inc.

www.xylem.com/bellgossett Xylem and Bell & Gossett are registered trademarks of Xylem Inc. or one of its subsidiaries. All other trademarks or registered trademarks are property of their respective owners.

© 2024 Xylem Inc. BG-e1510X-NOM-0913 R1 October 2024

Learn more about e-1510X Smart Pumps:

(1532X) = e-1532** with hydrovar X/X+ technology

**No baseplate

