

# Outline Type "VIS"

200.G.12 / 13

Submersible/ Submersible with Well Head

**Model: VIS Submersible Outline (200.G.12)**

Motor Data  
MFG: \_\_\_\_\_  
HP: \_\_\_\_\_  
Phase: \_\_\_\_\_  
NEMA: \_\_\_\_\_

Furnished By: \_\_\_\_\_  
RPM: \_\_\_\_\_  
Cycle: \_\_\_\_\_  
Voltage: \_\_\_\_\_

WEIGHT  
Pump: \_\_\_\_\_ lbs.  
Motor: \_\_\_\_\_ lbs.  
Barrell: \_\_\_\_\_ lbs.  
Misc: \_\_\_\_\_ lbs.  
Total: \_\_\_\_\_ lbs.

All Dimensions in inches

*VIS Outline*

Customer: \_\_\_\_\_  
Customer P.O.: \_\_\_\_\_  
Branch Order No.: \_\_\_\_\_  
Item: \_\_\_\_\_  
Service: \_\_\_\_\_

Pump Size	Stages	Imp. Dia.	BHP	Quantity
Liquid	GPM	TDH	Sp. Gr.	Temperature
Bowl Bearing				

Special Construction

\_\_\_\_\_  
Certified Correct

For Approval  
 For Record

By: \_\_\_\_\_  
Date: \_\_\_\_\_

Shop Order #	Rev.	Date

**Model: VIS-WF (200.G.13)  
Threaded Well Head**

Pipe Size "A" NPT	"B"	"C"	"D"	"E"
2	5.81	7.13	18	0.63
2.5	5.50	7.00	18	0.63
3	5.63	7.25	18	0.63
4	6.12	7.88	20	0.63
5	6.56	8.50	22	0.63
6	7.13	8.94	22	0.63

Motor Data  
MFG: \_\_\_\_\_  
HP: \_\_\_\_\_  
Phase: \_\_\_\_\_  
NEMA: \_\_\_\_\_

Furnished By: \_\_\_\_\_  
RPM: \_\_\_\_\_  
Cycle: \_\_\_\_\_  
Voltage: \_\_\_\_\_

WEIGHT  
Pump: \_\_\_\_\_ lbs.  
Motor: \_\_\_\_\_ lbs.  
Barrell: \_\_\_\_\_ lbs.  
Misc: \_\_\_\_\_ lbs.  
Total: \_\_\_\_\_ lbs.

All Dimensions in inches

*VIS-WF Outline*

Customer: \_\_\_\_\_  
Customer P.O.: \_\_\_\_\_  
Branch Order No.: \_\_\_\_\_

Item: \_\_\_\_\_  
Service: \_\_\_\_\_

Pump Size	Stages	Imp. Dia.	BHP	Quantity
Liquid	GPM	TDH	Sp. Gr.	Temperature
Bowl Bearing	Bowl Shaft Dia.	Column Size	No. of Column Piece	

Notes  
1 All Dimensions are in inches unless otherwise stated.  
2 Velocity past motor to insure sufficient cooling:  
= \_\_\_\_\_ Ft. / Sec

Special Construction

\_\_\_\_\_  
Certified Correct

For Approval  
 For Record

By: \_\_\_\_\_  
Date: \_\_\_\_\_

Shop Order #	Rev.	Date