TECHNICAL BROCHURE

BRJRJBB

FEATURES

- **Packages include:** 12 volt pump, float switch, 10 amp battery charger, check valve, pipe fittings and battery box.
- System requires minimum 105 amp deep cycle marine battery (not included).
- Automatic start-up, self-charging design and indicator lights on charger.
- Alarm sounds when pumping and battery won't charge.
- Designed to provide emergency backup service for primary pump in the event of a power outage. Will also operate if main pump can't keep up with inflow.



RJBB/RJBB2

BATTERY BACKUP SUMP PUMPS WASTEWATER



Red Jacket Water Products

RJBB PERFORMANCE CHART

Discharge Height	GPH	Battery Life
5'	1380	9 hrs.
10'	900	9 hrs.
13'	480	11 hrs.

RJBB2 PERFORMANCE CHART

Discharge Height	GPH	Battery Life
5'	2250	7 hrs.
10'	1500	8 hrs.
13'	1000	9 hrs.



Standard Installation

NOTE: *PRIMARY PUMP NOT INCLUDED.



Xylem Inc. 2881 East Bayard Street Ext., Suite A Seneca Falls, NY 13148 Phone: (866) 325-4210 Fax: (888) 322-5877 www.xyleminc.com/brands/redjacketwaterproducts

Red Jacket Water Products are trademarks of Xylem Inc. or one of its subsidiaries. © 2012 Xylem Inc. BRJRJBB May 2007