

STANDARD PRODUCT OFFERING

THE PROVIDED LIST IS INTENDED TO ACT AS AN OVERVIEW OF THE "BUILD AMERICA, BUY AMERICA ACT" COMPLIANCE STATUS FOR OUR STANDARD PRODUCT OFFERING.

- LOCATE THE MODEL NUMBER IN THE FIRST COLUMN AND SEE THE CURRENT BABA STATUS
- IF Y (YES) OUR CURRENT PRODUCT IS BABA COMPLIANT BUT MAY REQUIRE A "SPECIAL DESIGNATOR" ADDED TO THE END OF THE PART NUMBER TO ENSURE ALL DOMESTIC PARTS ARE USED. **EXAMPLE: STANDARD PRODUCT 261-00069012-000 (MAY USE IMPORT COMPONENT), 261-00069012-000B BABA COMPLIANT**
- IF "N" (NO) PLEASE SEE THE ALTERNATE PRODUCT SMITH-BLAIR OFFERS. THIS ALTERNATE WILL WORK IN THE APPLICATION BUT MAY UTILIZE DIFFERENT MATERIAL CONSTRUCTION. PLEASE LOOK FOR THE ALTERNATE MODEL NUMBER TO SEE THE SIZES OFFERED AND IF A SPECIAL DESIGNATOR IS REQUIRED.

PLEASE CONTACT SMITH-BLAIR ENGINEERING OR CUSTOMER SERVICE TO SEE IF A SPECIAL FABRICATION IS AVAILABLE THAT IS BABA COMPLIANT AND CORRECT FOR YOUR APPLICATION

| MODEL | PRODUCT DESCRIPTION | BABA Status | SIZES AVAILABLE | SPECIAL DESIGNATOR (if required) | ALTERNATE (see model number indicated) | COMMENTS |
|---------------|---|-------------|-----------------|----------------------------------|--|------------------------------------|
| REPAIR CLAMPS | | | | | | |
| 221 | Full Circle Repair Clamps, Single Band | N | | | 261 | 261 ONLY AVAILABLE IN 7-1/2" WIDTH |
| 226 | Full Circle Repair Clamps, Single Band | N | | | 261 | |
| 227 | Full Circle Repair Clamps, Double Band | N | | | 262 | |
| 228 | Full Circle Repair Clamps, Triple Band | N | | | 263 | |
| 229 | Full Circle Collar Leak Clamps, Single Band | N | | | 269 | |
| 238 | Full Circle Repair Clamps, Single Band, Tapped | N | | | 264 | |
| 239 | Full Circle Repair Clamps, Double Band, Tapped | N | | | 265 | |
| 244 | Full Circle Redi-Clamps | N | | | | |
| 245 | Redi-Clamps, Partial Coverage | N | | | | |
| 246 | Pipe Repair Clamps, Double Band | N | | | | |
| 247 | Full Circle Redi-Clamps, All 304 SS | N | | | | |
| 248 | Redi-Clamps, All 304 SS | N | | | | |
| 256 | Full Circle Repair Clamps, Single Band, All 304 SS | N | | | | |
| 257 | Full Circle Repair Clamps, Double Band, All 304 SS | N | | | | |
| 261 | Full Circle Repair Clamps, Single Band, All 304 SS | Y | ALL SIZES | B | | |
| 262 | Full Circle Repair Clamps, Double Band, All 304 SS | Y | ALL SIZES | B | | |
| 263 | Full Circle Repair Clamps, Multi-Band, All 304 SS | Y | ALL SIZES | B | | |
| 264 | Tapped Full Circle Repair Clamps, Single Band, All 304 SS | Y | ALL SIZES | B | | |
| 265 | Tapped Full Circle Repair Clamps, Double Band, All 304 SS | Y | ALL SIZES | B | | |
| 267 | Full Circle Repair Clamp, Carbon Steel, HigherPressure | Y | ALL SIZES | B | | |
| 268 | Full Circle Repair Clamp, Stainless Steel, HigherPressure | Y | ALL SIZES | B | | |
| 269 | Full Circle Collar Leak Clamps, Single Band | Y | ALL SIZES | B | | |

STANDARD PRODUCT OFFERING

| MODEL | PRODUCT DESCRIPTION | BABA Status | SIZES AVAILABLE | SPECIAL DESIGNATOR (if required) | ALTERNATE (see model number indicated) | COMMENTS |
|------------------------|---|-------------|-------------------|----------------------------------|--|--|
| 274 | Bell Joint Leak Clamp, Alloy | Y | 4"-12" | B | | ALL OTHER DOMESTIC SIZES FABRICATED FROM STEEL |
| 281 | Full Circle Wide Range Repair Clamp | N | | | | |
| SERVICE SADDLES | | | | | | |
| 311 | Service Saddles, Single Bale, Ductile Iron | N | | | | |
| 313 | Service Saddles, Double Bale, Ductile Iron | N | | | 383 | |
| 315 | Service Saddles, Single Bale, Ductile Iron | N | | | | |
| 317 | Service Saddles, Double Straps, Ductile Iron | Y | 4"-8", 12" | B | 387 | 12" LIMITED TO TAP UNDER 1-1/4" 10" AND 12" W/2" TAPS AND SMALLER EXPECTED THIRD QUARTER 2024 |
| 325 | Bronze Service Saddles, Extra Wide 304 SS Strap | Y | ALL SIZES | | | BABA COMPLIANT, AIS NOT APPLICABLE |
| 331 | Repair Service Saddle, Double Bale, EpoxyCoated DI Body | N | | | | |
| 357 | Service Saddle, Stainless Steel Straps, DI Body | N | | | | |
| 362 | Service Saddles, DI Body with Epoxy CoatedStraps | N | | | | |
| 366 | Service Saddles for Large Dia., DI Body, Epoxy Coated Straps | N | | | | |
| 371 | Service Saddles, Single Stud, All 304 SS | Y | ALL SIZES | B | | |
| 372 | Service Saddles, Double Stud, All 304 SS | Y | ALL SIZES | B | | |
| 377 | Service Saddles, Wide Range, Double Stud, All 304 SS | N | | | | |
| 383 | Steel Fabricated Service Saddles, Double Steel Fabricated Strap | Y | 6" and larger | | | FABRICATED STEEL BODY AND STRAPS |
| 387 | Steel Fabricated Service Saddles, Double SS Straps | Y | 6" and larger | B | | FABRICATED STEEL BODY AND SS STRAPS |
| 397 | Service Saddles for DI Sized pipe and PVC | Y | 4"-8", 12" | B | | |
| COUPLINGS | | | | | | |
| 411 | Steel Couplings | Y | 3" AND LARGER | B | | COMPONENT MATERIAL MAY VARY BY SIZE |
| 413 | Steel Transition Couplings | Y | 2" AND LARGER | B | | COMPONENT MATERIAL MAY VARY BY SIZE |
| 415 | Steel Reducing Couplings, Alloy Bolts & Nuts | Y | 3" AND LARGER | B | | COMPONENT MATERIAL MAY VARY BY SIZE |
| 416 | Steel Insulating Couplings, Single Boot, AlloyBolts & Nuts | Y | 3" AND LARGER | B | | COMPONENT MATERIAL MAY VARY BY SIZE |
| 418 | Tee Couplings, Smaler Diameter Pipe | N | | | | |
| 421 | Top Bolt Couplings | Y | 2"-12" | B | | NO OFFERING FOR BABA 10" & 12" OVERSIZED |
| 422 | Top Bolt Long Sleeve Couplings | Y | 2" 12" | B | | NO OFFERING FOR BABA 10" & 12" OVERSIZED |
| 441 | OMNI Cast Couplings, Straight & Transition | Y | 3"-12" (DI TO DI) | B | | SOME FLANGE COMBINATIONS REQUIRE FABRICATED STEEL COMPONENTS |
| 441 | Components | Y | 3"-12" (DI TO DI) | B | | SOME COMBINATIONS REQUIRE FABRICATED STEEL COMPONENTS |
| 442 | OMNI Long Sleeve Couplings, Straight & Transition | Y | 4"-12" (DI TO DI) | B | | ALL SLEEVES ARE FABRICATED STEEL; SOME FLANGE COMBINATIONS REQUIRE FABRICATED STEEL COMPONENTS |

STANDARD PRODUCT OFFERING

| MODEL | PRODUCT DESCRIPTION | BABA Status | SIZES AVAILABLE | SPECIAL DESIGNATOR (if required) | ALTERNATE (see model number indicated) | COMMENTS |
|----------------------------------|--|-------------|-------------------|----------------------------------|--|---|
| 442 | Components | Y | 4"-12" (DI TO DI) | B | | SOME COMBINATIONS REQUIRE FABRICATED STEEL COMPONENTS |
| 461 | Quantum Couplings | N | | | 421 | |
| 462 | Quantum Couplings, 12" Sleeve | N | | | 422 | |
| 481 | Steel End Cap | Y | 3" AND LARGER | B | | COMPONENT MATERIAL MAY VARY BY SIZE |
| 482 | OMNI Cast Pipe End, Alloy Bolts & Nuts | Y | 3"-12" (DI ONLY) | B | 481 | SOME COMBINATIONS REQUIRE FABRICATED STEEL COMPONENTS |
| 482 | Components | N | | | | |
| 525 | Compression Couplings | N | | | | |
| TAPPING SLEEVES | | | | | | |
| 622 | Carbon Steel Tapping Sleeve | Y | | B | | |
| 623 | Fabricated MJ Joint Tapping Sleeves | Y | | B | | |
| 624 | Fabricated MJ Joint Tapping Sleeves | Y | | B | | |
| 625 | Tapping Sleeves For Concrete Cylinder Pipe | Y | | B | | |
| 626 | Weld On Tapping Sleeves | Y | | B | | |
| 627 | Tapping Sleeves, Fabricated Weld On Outlet | Y | | B | | |
| 662/663 | Stainless Steel Tapping Sleeves with MJ Outlet | Y | | B | | |
| 663WR | Wide Range All SS Tapping Sleeves (availabe w MJ Outlet) | Y | ALL SIZES | B | | |
| 664/665 | Stainless Steel Tapping Sleeves with MJ Outlet | Y | | B | | |
| 68X | Line Stop Outlets for Tapping Sleeves | Y | | B | | |
| FLANGED COUPLING ADAPTERS | | | | | | |
| 912 | OMNI Flanged Coupling Adapters | N | | | 913 | 913 FABRICATED STEEL |
| 912 | OMNI Components | N | | | 913 | 913 FABRICATED STEEL |
| 913 | Flanged Coupling Adapters, Steel | Y | | B | | |
| 914 | Reducing Flanged Coupling Adapters | Y | | B | | |
| 921 | Top Bolt Flanged Coupling Adapters | Y | | B | | |
| 922 | Top Bolt Long Sleeve Flanged Coupling Adapters | Y | | B | | |
| 926 | Flexible Meter Coupling | N | | | | |
| DISMANTLING JOINTS | | | | | | |
| 971 | Non Restrained Dismantling Joints | Y | | B | | |
| 972 | Heavy Duty Restrained Dismantling Joints | Y | | B | | |
| 973 | Restrained Dismantling Joints | Y | 4"-12" | B | | |
| 975 | Restrained Dismantling Joints | Y | | B | | |
| EXPANSION JOINTS | | | | | | |

STANDARD PRODUCT OFFERING

| MODEL | PRODUCT DESCRIPTION | BABA Status | SIZES AVAILABLE | SPECIAL DESIGNATOR (if required) | ALTERNATE (see model number indicated) | COMMENTS |
|-------------------|--|-------------|---------------------------------|----------------------------------|--|-------------------------------------|
| 611 | Expansion Joints, Single End 10" Expansion | Y | | B | | |
| 612 | Expansion Joints, Double End 10" Expansion | Y | | B | | |
| RESTRAINTS | | | | | | |
| EZW | Straight Seal & Restraint Couplings | N | 4"-12" | | 470 SERIES W/"B" | |
| EZW | Reducing Seal & Restraint Couplings | N | 4"-12" | | 470 SERIES W/"B" | |
| EZW | Seal & Restraint Line Caps | N | | | NOT AVAILABLE | |
| EZW | Flanged Coupling Adapters | N | 4"-12" | | 911 OR 920 W/"B" | |
| 471 | Pipe-Lock Straight Restraint Sleeve Couplings (DI) | Y | 4"-30" | B | | |
| 472 | Pipe-Lock Straight Restraint Sleeve Couplings (PVC/HDPE) | Y | 4"-24" | B | | |
| 473 | Pipe-Lock Straight Restraint Sleeve Couplings | Y | PVC END 4"-24" DI END 4"-30" | B | | PVC END IS APPLICABLE TO HDPE |
| 477 | Pipe-Lock Straight Restraint Sleeve (sleeve only) | Y | 4"-48" | D | | |
| 911 | Flange-Lock Flanged Coupling Adapter (DI) | Y | 4"-30" | B | | |
| 920 | Flange-Lock Flanged Coupling Adapter (PVC/HDPE) | Y | 4"-24" | B | | |
| 923 | Flange-Lock Flanged Coupling Adapter (body only) | Y | | D | | |
| 907 | Restraint Plates | Y | ALL SIZES | NOT APPLICABLE | | 2" ≥ THICK USE STANDARD PART NUMBER |